



**Den Braven**

## Technical Data Sheet

### SX Premium Mortar Repair Cement

Ready mixed and easy to use



#### Product Description

A ready to use high quality hardening joint repair filler based on acrylic dispersions and additives. Specifically developed to repair damaged masonry joints quickly without the need to mix sand and cement. Will adhere perfectly without primer even on damp surfaces.

#### Benefits

- Ready to use
- Adheres without primer even on slightly damp surfaces
- Interior and exterior applications
- Easy to apply
- Easy to clean
- Non corrosive towards metals

#### Applications

Suitable for interior and exterior applications for the restoration and repair of damaged masonry between brick and stone work. Also for repairing cracks and damaged stone edges. Can be used to seal between tiles, stones, brick slips and pointing around lead flashing.

#### Directions Of Use

Cut the cartridge seal and screw on the pre-cut 'V' notched nozzle. Using a skeleton gun, apply the product into the gap ensuring a good solid fill. After 5 minutes press the mortar into the joint using an appropriate jointing tool and then after a further 5-10 minutes remove

excessive material from stone or brickwork using a hand brush or wet sponge.

#### Additional information

Application temperature		+5°C to +40°C
Base		Acrylic dispersion
Density	ISO 1183-1	1,66 g/ml
Flow	ISO 7390	< 2mm
Frost resistance during transportation		Up to -15°C
Shorea hardness	DIN 53505	80
Shrinkage		5%

*These are typical values*

#### Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- \*Exterior applications only in good dry weather conditions for at least 5 hours after application
- Not suitable for movement joints

#### Surface Preparations and Finishing

Surfaces must be clean and free from dust and grease. Apply in temperatures of +5°C to +40°C.

#### Cleaning

Tools and hands can be cleaned water. Issue 2/29.04.16/0317.1.DBS

#### Colour(s)

- Cement Grey

#### Packaging

- Cartridge

*For product specifications, please refer to the Product Detail Page*



**Den Braven**

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

20-05-2024  
03:23:28  
CEST



## Technical Data Sheet

### SX Premium Mortar Repair Cement

Ready mixed and easy to use

#### Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

#### Certifications

	<p>A+ French VOC Regulation</p>
---	---------------------------------

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

#### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.