



Technical Data Sheet

Zwaluw Woodsealer

Protective coating for plywood



Product Description

Zwaluw Woodsealer is a fluid ready-to-use coating based on acrylic dispersion. The product cures due to evaporation of water to form a weatherproof and durable coating.

Benefits

- For use on rip and cross cut sides and full surfaces of wood
- Ready to use
- Paintable with water based and synthetic paints
- Almost odourless
- Easy to apply and clean
- Non corrosive towards metals

Applications

Zwaluw Woodsealer was specifically developed as a durable protective coating for rip and cross cut sides and full surfaces of plywood and laminated wooden sheet material. Especially suitable to preserve spruce, meranti, merbau and laminated wooden sheet material (triplex, multiplex). Zwaluw Woodsealer is a SHR certified coating.

Directions Of Use

Apply at least two coats of Woodsealer evenly with a paint brush or roller covering 400 g/m² per layer.

Additional information

Application temperature		+10°C to +40°C
Base		Acrylic dispersion
Density	ISO 1183-1	1,15 g/ml
Flow	ISO 7390	< 2mm
Frost resistance during transportation		Up to -15°C
Temperature resistance		-20°C to +75°C
Thickness		Minimum 2 coats
Usage		400g/m ²

These are typical values

Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Application temperature +10°C to +40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Substrates to be cleared of all loose particles, absorbent substrates do not need to be absolutely dry. Always test adhesion prior to application.

Paintability

Zwaluw Woodsealer is paintable when the sealant is fully dried. During curing the product will show shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatibility with paint prior to application.

Cleaning

Tools should be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

Colour(s)

- White



Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw Woodsealer

Protective coating for plywood

Packaging

- Can

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life is up to 18 months from production date, stored in a dry place.

Certifications

	SKH
--	-----

Health & Safety

Product Safety Data Sheet must be read and understood before use.

These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.