



Den Braven

Technical Data Sheet

Zwaluw Acryl Exterior+

High quality fast rain resistant acrylic sealant for interior and exterior use



Product Description

Acryl Exterior+ is a high quality acrylic sealant quickly water resistant after application. After application the product forms a soft plasto elastic rubber once the water evaporates from the sealant.

Benefits

- Very quickly rain resistant after application
- Suitable for exterior use
- High elongation at break and high movement accommodation
- Paintable with water based- and synthetic paints
- Perfect adhesion without the use of a primer, even on damp substrates
- Almost odourless
- Easy to apply
- Easy to clean
- Non corrosive towards metals
- Excellent tooling properties

Applications

Acryl Exterior+ was specifically developed for connection joints between windowsills, stairs, ceilings, walls, thresholds, panels, aerated concrete, plasterboard, limestone, wooden and metal window frames, concrete and brickwork for interior and exterior applications. As the sealant is so quickly rain resistant after application, there are more possible applications.

Directions Of Use

A well-designed joint is a joint with a sufficient width so it would be able to take and process the movement of the adjacent building elements. The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width up to 10 mm is 1:1, with a minimum of 5 mm in width and depth. For joints wider than 10 mm, the depth is the width divided by 3 plus 6 mm. For further questions please contact our technical service.

Additional information

100 % modulus	DIN 53504 S2	0,10 N/mm ²
Application temperature		+5°C to +40°C
Base		Acrylic dispersion
Density	ISO 1183-1	1,57 g/ml
Frost resistance during transportation		Up to -15°C
Shorea hardness	DIN 53505 / ISO 868	10
Skin formation	DBTM 16	10 minutes @ +23°C/50% RH
Temperature resistance		-20°C to +75°C
Tensile strength	DIN 53504	0,10 N/mm ²

These are typical values

Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Although the product is rain resistant, it will not withstand heavy driving rain and hail during curing
- Not suitable for continuous exposure to water

Surface Preparations and Finishing

Application temperature +5°C to +40°C (applies to environment and substrate). All substrates must be solid, clean, dry, and free of grease and dust. Substrate to be cleaned from all loose particles, porous substrate do not require to be absolutely dry. Very porous substrates like: Gypsum, aerated concrete, limestone, etc, need to be primed

Zwaluw Acryl Exterior+

High quality fast rain resistant acrylic sealant for interior and exterior use

with a mixture of 1 part Acryl Exterior and 2 parts water. Adhesion tests prior to application are recommended. Finish and smooth with water.

Paintability

Acryl Exterior+ is paintable when fully dry. During curing product will show shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatability with paint prior to application.

Cleaning

Tools should be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

Colour(s)

- White

Packaging



- Cartridge



For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 18 months after production date, stored in a dry place.

Certifications

	<p>EN 15651-1: F-EXT-INT 12.5P</p>
	<p>A+ French VOC Regulation</p>

	<p>Emicode EC1 Plus</p>
	<p>SNJF FACADE 12.5P</p>

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.