



Den Braven

Technical Data Sheet

Zwaluw Montagefix-N

Versatile fast setting adhesive



Product Description

Zwaluw Montagefix-N is a versatile construction adhesive based on neoprene which cures by evaporation of solvents to a strong and durable bond.

Benefits

- Suitable for porous and non-porous substrates
- Adheres to most building materials

Applications

Zwaluw Montagefix-N was developed for bonding of skirting boards, panels, chipboard, uPVC, all kinds of wood, metal and ceramic on masonry, concrete and stone.

Directions Of Use

Apply the adhesive in equal measure in stripes. The material must be put into place by shoving and pushing firmly. For faster bonding, bond both parts together and take them apart again. Let dry for 5 minutes and close the connection. It may be necessary to support the connection up to 24 hours. For the best results at least one of the two surfaces must be porous. Do not apply in dots!

Additional information

Application temperature		+5°C to +25°C
Base		Polychloroprene
Density		1,10 g/ml
Frost resistance during transportation		Up to -15°C
Open time	@ +23°C / 50% RH	12 minutes
Solid contents		57%
Temperature resistance		-30°C to +90°C
Tensile strength		0,50 N/mm ²
Usage	6 mm bead	10m per

These are typical values

Limitations

- Not suitable for PE, PP, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Application temperature: +5°C to +25°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Zwaluw Montagefix-N adheres well without the use of primer to most non porous substrates. Remove paint on the bonding surfaces. Always test adhesion prior to application.

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

- Beige

Packaging

- Cartridge

For product specifications, please refer to the Product Detail Page



Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw Montagefix-N

Versatile fast setting adhesive

Shelf Life

Store at temperatures between + 5°C and + 25°C. The shelf life of the product is 12 months from date of manufacture if stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites.

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik's written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Arkema Middle East DMCC
Unit 1108 JBC 3 Tower, Cluster Y, Jumeirah Lakes Towers, P.O. Box 336393 Dubai
T +971 48751704 | E bostik.mena-info@bostik.com

09-05-2024
11:37:33
MDT