



Den Braven

Technical Data Sheet

Zwaluw Sili-Kill®

Removes cured silicone residue



Product Description

Zwaluw Sili-Kill® was specifically developed to remove cured silicone residue.

Benefits

- Removes hardened silicone residues

Applications

Directions Of Use

Cut the silicone sealant and remove as much as possible with a sharp knife. Shake Den Braven Sili-Kill® well before use. Apply excess amounts of Zwaluw Sili-Kill® to the cured silicone residue. After 20-30 minutes the sealant silicone residue can easily be removed with a putty knife or a wooden spatula for vulnerable substrates. If necessary repeat the treatment. Afterwards wash with water and soap and let dry.

Additional information

| | | |
|--|--|---------------|
| Application temperature | | +5°C to +30°C |
| Consistency | | Paste |
| Density | | 0,80 g/ml |
| Frost resistance during transportation | | Up to -15°C |

These are typical values

Limitations

Surface Preparations and Finishing

Before using the Zwaluw Sili-Kill® refer to the Health & Safety Sheet. Contact Den Braven for a full recommendation. Clean hands with Zwaluw Handclean.

Cleaning

Colour(s)

- Transparent

Packaging

- Bottle

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life is up to 24 months from production date, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Den Braven Sealants S.A. (Pty) Ltd.
2 Highview Boulevard, Ferndale Extension 26, Randburg, Gauteng
T +27 117923830 | E sales@denbraven.co.za

18-05-2024
11:03:24
MDT