



# Den Braven

## Technical Data Sheet

### Zwaluw Gluescrews

Versatile solvent based adhesive



### Product Description

Zwaluw Gluescrews is a fast curing construction adhesive based on SBR rubber for interior use which cures by evaporation of solvents to a strong and durable bond. Remark: MSDS available on request

### Benefits

- Versatile fast curing contact adhesive
- Free of toluene
- Suitable for EPS and XPS
- Suitable for porous and non-porous substrates
- Adheres to most building materials

### Applications

Zwaluw Gluescrews was developed for bonding of skirting boards, panels, chipboard, uPVC, all kinds of wood, metal and ceramic on masonry, concrete and stone.

### Directions Of Use

Apply the adhesive vertically. The material must be put into place by shoving and pushing firmly. For faster bonding, bond both parts together and take them apart again. Let dry for 5 minutes and close the connection. It may be necessary to support the connection for up to 24 hours. For the best results at least one of the two surfaces must be porous. Do not apply in dots!

### Additional information

Application temperature		+5°C to +25°C
Base		Styrene-butadiene rubber
Curing time	+23°C / 50% RH	72 hours
Density		1,40 g/ml
Frost resistance during transportation		Up to -15°C
Open time		3-5 minutes
Skin formation		3-5 minutes
Solids		83%
Temperature resistance		-30°C to +70°C
Usage		300-600 g/m²

*These are typical values*

### Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

### Surface Preparations and Finishing

Application temperature: +5°C to +30°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Zwaluw Gluescrews adheres perfectly without the use of primer to most non porous substrates. Porous substrates to be pre-treated with Zwaluw Universal Primer. Always test adhesion prior to application.

### Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

### Colour(s)

- Beige



# Den Braven

Better  
results  
through  
knowledge

## Technical Data Sheet

### Zwaluw Gluescrews

Versatile solvent based adhesive

#### Packaging

- Cartridge

*For product specifications, please refer to the Product Detail Page*

#### Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life is up to 12 months from date of production, stored in a dry place.

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

#### Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Den Braven Sealants S.A. (Pty) Ltd.  
2 Highview Boulevard, Ferndale Extension 26, Randburg, Gauteng  
T +27 117923830 | E sales@denbraven.co.za

18-04-2024  
10:28:24  
MDT