



Technical Data Sheet

Zwaluw Universal Primer

A ready to use primer to improve the adhesion of hybrid-, PU- & silicon-sealants to many porous and non-porous substrates



Product Description

Universal Primer is a ready to use primer to improve the adhesion of hybrid-, PU- & silicon-sealants to many porous and non-porous substrates. Primer containing solvents based on polyurethane.

Benefits

• Ready to Use

Applications

For sealants and adhesives based on MS-polymer, PU and silicones.

Directions Of Use

On a clean, dry and dust free substrate. Cover substrate -where needed- with masking-tape. Shake or stir well before use. Apply the Universal Primer as an equal thin layer on the substrate with a brush. When the primer is dry, apply sealant or adhesive as soon as possible to prevent contamination of the substrate. General: Close packaging between use as the primer is sensitive to humidity.

Additional information

Application temperature	+0°C till +35°C
Density	1,35 g/ml
Frost resistance during transportation	Up to -15°C

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Transparent

Packaging

• Can

For product specifications, please refer to the Product Detail Page

Shelf Life

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not lable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness of this document. The product of between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held lable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

