



Den Braven

Technical Data Sheet

Zwaluw Single Cup Lifter

Ergonomically designed single cup vacuum pump with maximum capacity of 57 kg



Product Description

Zwaluw Suction Cup is an ergonomically designed 200mm single cup vacuum pump that provides a comfortable hold during lifting. Den Braven® QEA110G provides quick release from the surface due to the combination of the rubber pad and relief valve. The pump's plunger has a red indicator line to show the vacuum level when the lifter is in use. When the lifter is properly attached to the load's surface, the red line will be hidden inside the pump. Should the red line become visible during a lift, set down the load and re-pump until red line is again hidden.

Benefits

- Single handed operation
- Lightweight (1,36 kg)
- Cup diameter of 200 mm
- Lifting capacity of maximum 57 kg
- Comfortable grip
- Convenient vacuum indicator and release
- Superior lifting capacity performance
- Prevent injuries and increase productivity
- Built from durable ABS polymer
- Long-term durability and outstanding reliability
- Supplied with protective carrying case
- Safe for most surfaces

Applications

Zwaluw Suction Cup can be used to handle awkward loads on the building site and in a manufacturing environment for lifting and handling glass windows, counter tops, appliances, patio doors, vending machines, windshields, side lites, sheet metal, auto body panels, cladding insulated metal panels, etc.

Zwaluw Suction Cup use vacuum to lift and carry loads:

- A manual pump removes air from between the rubber pad and the contact surface.
- The red line on the pump's plunger serves as a vacuum indicator.

- A check valve allows the user to repump the cup without removing it from the contact surface.

- A release mechanism allows the cup to disengage completely.

Maximum Load Capacity includes a 3:1 safety factor and requires the following:

- Attachment to clean, smooth, non-porous flat surfaces.
- A minimum vacuum level of -59 kPa
- And a friction coefficient of 1.

This rating is based on tests of new hand cups attached to the upper, horizontal surface of static objects in ideal conditions. Many factors can reduce the capacity, including: lifting a load when the cup is attached to a vertical or inclined surface; or lifting a load that applies leverage to the cup.

Directions Of Use

Use the cup on clean, relatively smooth, non-porous surfaces, at temperatures from - 10°C to + 40°C. Moisture or contaminants can reduce the slip resistance of the cup. The red-line indicator may not perform reliably at elevations above 1500 meters. To Attach Zwaluw Suction Cup at the load: • Position Zwaluw Suction Cup on the contact surface so the red line will be visible if it should appear while lifting the load. CAUTION: Test the cup for staining or deformation of load surfaces with light colors or soft coatings. • Pump the plunger until the Zwaluw Suction Cup attaches completely. When the red line is hidden, vacuum is ready for lifting. • Check the plunger frequently to make sure the cup remains securely attached. If the red line appears while lifting, set down the load immediately and pump the plunger until the red line is hidden again. To Release Zwaluw Suction Cup from the load: • Set the load on a secure support. • Press the valve release lever until the cup disengages completely. CAUTION: Remove the cup when not in use!

Limitations

- Do not use on dirty, rough, porous and wet surfaces

Surface Preparations and Finishing

Examine and test the cup regularly to make sure it does not exhibit the following faults: • cuts or damage to sealing edges of rubber pad • cracks or dents in handle or pump • reappearance of red line soon after attaching cup • sluggishness or dramatic changes in pump action • excessive glaze or stiffness of rubber pad • air filter missing from cup face • Correct any faults before using the cup



Den Braven

Den Braven Sealants S.A. (Pty) Ltd.
2 Highview Boulevard, Ferndale Extension 26, Randburg, Gauteng
T +27 117923830 | E sales@denbraven.co.za

01-05-2024
13:30:21
CEST



Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw Single Cup Lifter

Ergonomically designed single cup vacuum pump with maximum capacity of 57 kg

Cleaning

Remove the air filter from the cup face. Use Zwaluw Wipes to clean the cup. CAUTION: To prevent liquid from contaminating the pump, hold the cup face-down or cover the suction hole in the filter recess. Wipe all residue from the cup face. Allow the cup to dry and reinstall the air filter.

Colour(s)

- Black

Packaging

- Piece

For product specifications, please refer to the Product Detail Page

Shelf Life

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Den Braven Sealants S.A. (Pty) Ltd.
2 Highview Boulevard, Ferndale Extension 26, Randburg, Gauteng
T +27 117923830 | E sales@denbraven.co.za

01-05-2024
13:30:21
CEST