



# Den Braven

## Technical Data Sheet

### Zwaluw PU Stone Adhesive

High quality ready-to-use stone adhesive



#### Product Description

Zwaluw PU Stone Adhesive is a high quality ready to use polyurethane adhesive for bonding various types of stone. It is the adhesive to use when no water and/or electricity is available and one needs to work in a fast, clean and efficient manner.

#### Benefits

- Quick & clean application
- Stronger bond, tensile strength after one day > 7 N/mm<sup>2</sup>
- For use on multiple surfaces
- Simple, modern and labour friendly application
- Lower adhesive consumption due to thin bonding thickness
- Lighter than traditional mortars
- Lower transportation and storage costs
- Ready to use (no mixing)

#### Applications

Zwaluw PU Stone Adhesive was specifically developed for bonding non-bearing interior walls of gypsum, concrete, aerated concrete and lime stone blocks.

#### Directions Of Use

Canister temperature: +5°C to +30°C (recommended +15°C to +25°C) Application temperature (applies to environment and substrates): +5°C to +35°C (recommended +15°C to +25°C) For

adhering blocks with tongue and groove: Turn the applicator gun, with NBS-thread, upside down and affix a canister of foam to the applicator gun. We recommend a NBS Gold (see instructions in the gun box). Shake the canister vigorously prior to use at least 20 times. Turn canister upside down and apply the foam. 1. Unlock/open the screw at the rear of the gun by a third (1/3) in order to apply the PU Stone Adhesive with as much control as possible. 2. When bonding ribbon joints apply two beads of PU Stone Adhesive 20 mm in diameter as close as possible on both sides of the tongue. At least 80% of the block surface is covered with PU Stone Adhesive. You can check this by placing the second block and removing immediately. 3. Apply the blocks by moving slightly into place, avoiding the adhesive for an even distribution and prevention of bulging glue. 4. For bonding butt joints place the block vertically and place one bead of PU Stone Adhesive before placing the blocks. 5. Remove fresh excess foam immediately with Universal PU Cleaner. For adhering flat blocks: Turn the applicator gun, with NBS-thread, upside down and affix a canister of foam to the applicator gun. We recommend a NBS Gold (see instructions in the gun box). Shake the canister vigorously prior to use at least 20 times. Turn canister upside down and apply the foam. 1. Unlock/open the screw at the rear of the gun by a third (1/3) in order to apply the PU Stone Adhesive with as much control as possible. 2. When bonding ribbon joints apply two beads of PU Stone Adhesive 20 mm in diameter as close as possible on both sides of the tongue. At least 80% of the block surface is covered with PU Stone Adhesive. You can check this by placing the second block and removing immediately. 3. Apply the blocks by moving slightly into place, avoiding the adhesive for an even distribution and prevention of bulging glue. 4. For bonding butt joints place the block vertically and place one bead of PU Stone Adhesive before placing the blocks. 5. Remove fresh excess foam immediately with Universal PU Cleaner. In both application methods 80% block surface must be covered with PU Stone Adhesive. Protect eyes, wear gloves and protective gear. Floor-covering and furniture to be covered with paper or plastic foil. Only use in well ventilated areas. Storage and shelf life: Store canister upright between +5°C and +25°C. Pressurized container! Protect from sunlight and do not expose to temperatures exceeding +50°C. Do not pierce or burn, even after use. Contains flammable propellants. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking. For more information see Technical Bulletins in the Knowledge Base on our website [www.denbraven.com](http://www.denbraven.com).



Den Braven

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

18-05-2024  
14:45:17  
CEST



# Den Braven

## Technical Data Sheet

### Zwaluw PU Stone Adhesive

High quality ready-to-use stone adhesive

#### Additional information

Application temperature		+5°C to +35°C
Base		Polyurethane
Curing time		60-80 minutes
Temperature resistance		-40°C to +90°C

*These are typical values*

#### Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for permanent water load. Not suitable for use (eg filling) in cavities with insufficient moisture

#### Surface Preparations and Finishing

Substrates must be clean and free of dust, oil and grease. It is important to moisten substrates slightly before use as this improves adhesion and finished cell structure of the foam.

#### Paintability

Can be painted or covered with sealant/plaster when fully cured.

#### Cleaning

Fresh foam can be removed immediately with Zwaluw Universal PU-Cleaner. After curing surplus foam can be removed with a knife or spatula and the foam surface can be finished.

#### Colour(s)

- Beige

#### Packaging


- Can

*For product specifications, please refer to the Product Detail Page*

#### Shelf Life

If kept stored in a cool, dry place, in unopened original packaging, between +5°C and +25°C, shelf life is up to 18 months from production date. Store the canisters in an upright position.

#### Certifications

	FEICA member
	A+ French VOC Regulation

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites.

#### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik's written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

18-05-2024  
14:45:17  
CEST