



# Technical Data Sheet

### Tectane Leak Detector DVGW Certified



# **Product Description**

Effortlessly allows you to find any leaking spots on screwed and flanged joints, conduits and welds under internal pressure. Does not form harmful compounds with gases, such as carbon dioxide (CO2), propane, butane, acetylene, compressed air, town and natural gas, nitrogen or fluorinated hydrocarbons.

#### **Benefits**

- Tested in Germany DIN 30657 (DVGW)
- Not flamable
- Anti-corrosive
- · Non-toxic and environmentally-friendly
- Skin tolerant
- · Saves energy and costs

### **Applications**

### **Directions Of Use**

Shake the aerosol vigorously. Expose suspected spots and spray them. Leaking spots are indicated by extremely heavy foam formation. NB: Do not use for testing pipes conducting oxygen.

#### Additional information

Base	Aqueous surfactant solution
Density	1.007
Extrusion rate gs	5.8
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	5.1
Pressure at 50c bar	6.6

These are typical values

### Limitations

### Surface Preparations and Finishing

### Cleaning

# Colour(s)

Colourless

### Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

# Shelf Life

Store between +5°C and +25°C in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

#### Certifications

DIN EN 14291
DIN LIN 14231

### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites







# Technical Data Sheet

### Tectane Leak Detector DVGW Certified

### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

