



Technical Data Sheet

Zwaluw Mixed Finisher Spray Joint sealant finishing adiative



Product Description

Zwaluw Mixed Finisher is a ready mixed neutral universal additive for the wet tooling of sealants in joints. Zwaluw Mixed Finisher is more than 99% Biodegradable.

Benefits

- · Ready to use
- · Pre mixed to the correct ratio
- 99% Biodegradable

Applications

Zwaluw Mixed Finisher was developed for the wet tooling of sealants in joints. Before use always mix thoroughly. After application of the sealants the surface of the joints and the neighbouring surfaces must be moistened with Zwaluw Mixed Finisher Spray. The joint may be tooled using a spatula, a putty knife or PVC pipe. After smoothing the joint can be finished with a finger dipped in Zwaluw Mixed Finisher Spray.

Directions Of Use

Additional information

Application temperature	+5°C to +40°C
Density	1,00 g/ml
Frost resistance during transportation	Up to -15°C
pH value	pH = 7,1

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Transparent

Packaging

• Bottle

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life up to 12 months from production date, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

