



Den Braven

Technical Data Sheet

SX Premium Instant Plaster Filler

Non-shrinking, ultra-light, ready mixed filler



Product Description

A non-shrinking, ultra-light, ready mixed filler for filling and repairing cracks and holes in walls and ceilings. It is quick drying and can be over-painted with emulsion based paint 10-20 minutes after application, subject to ambient conditions. After curing the product can be sanded.

Benefits

- Ultra lightweight
- Non shrinking
- Paintable with water based and synthetic paints
- Sandable after curing
- Easy to apply
- Easy to clean
- Non corrosive towards metals

Applications

For filling joints and screw holes in plasterboard walls and ceilings.
For filling and repairing holes and in static joints in concrete, brickwork and plaster.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the filler into the gap or joint ensuring a good solid fill. Smooth off using a putty knife.

Additional information

Application temperature		+5°C to +30°C
Base		Acrylic dispersion
Density		0,60 g/ml
Flow	ISO 7390	< 2 mm
Frost resistance during transportation		Up to -15°C
Shrinkage		<5%
Skin formation	@ +23°C/50% RH	5 minutes
Temperature resistance		-20°C to +75°C

These are typical values

Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Surfaces must be clean, dry and free from dust, grease and other loose material. Finish with a wet taping knife or wet trowel.

Paintability

Can be over-painted 10-20 minutes after application, subject to ambient conditions. Painting over with highly filled emulsion paint can cause craze cracking on the paint surface. Due to the variety of paint compositions, we do recommend preliminary tests for compatibility.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.
Issue12/29.04.16/0141.11.DB

Colour(s)

- White



Den Braven

Bostik Singapore
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore
T +65 6419 9161 | E

05-05-2024
21:36:18
CEST



Den Braven

Better
results
through
knowledge

Technical Data Sheet

SX Premium Instant Plaster Filler

Non-shrinking, ultra-light, ready mixed filler

Packaging



- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

Certifications

	EN 13963: 1A
	M1
	Emicode EC1 Plus

Health & Safety

Product Safety Data Sheet must be read and understood before use.
These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Bostik Singapore
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore
T +65 6419 9161 | E

05-05-2024
21:36:18
CEST