



**Den Braven**

## Technical Data Sheet

### Zwaluw Plasterboard-Filler

Ultra lightweight ready to use filler



#### Product Description

Zwaluw Plasterboard-Filler is virtually a non shrinking, ready to use ultra light, ready mixed filler and spackling compound for filling and repairing cracks and holes in walls and ceilings.

#### Benefits

- Ultra lightweight
- Almost non-shrinking
- Paintable with water based- and synthetic paints
- Sandable after curing
- Easy to apply and clean
- Non corrosive towards metals

#### Applications

Zwaluw Plasterboard Filler was specifically developed for filling one time joints and screw holes in plasterboard walls and ceilings for interior applications. Also for one time filling, repairing and smoothing of holes and cracks in concrete, plaster, brickwork and stucco layers.

#### Directions Of Use

For best results, the product should be applied without pressure.

#### Additional information

Application temperature		+5°C to +30°C
Base		Acrylic dispersion
Density		0,60 g/ml
Flow	ISO 7390	< 2 mm
Frost resistance during transportation		Up to -15°C
Shrinkage		<5%
Skin formation	@ +23°C/50% RH	5 minutes
Temperature resistance		-20°C to +75°C

*These are typical values*

#### Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

#### Surface Preparations and Finishing

Application temperature +5°C to +30°C (applies to environment and substrate). All surfaces must be solid, clean, free of dust and grease. Substrates to be cleared of all loose particles, porous substrate do not need to be dry. Very porous substrates like: gypsum, airated concrete, limestone, etc, need to be primed with a mixture of 1 part Zwaluw Plasterboard-Filler and 2 parts water. Adhesion tests prior to application are recommended. Finish and smooth with a wet spatula.

#### Paintability

Zwaluw Plasterboard-Filler is paintable when fully dry. During curing product will show minimal shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatability with paint prior to application.

#### Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.



**Den Braven**

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

04-05-2024  
17:02:56  
MDT



Den Braven



Technical Data Sheet

Zwaluw Plasterboard-Filler  
Ultra lightweight ready to use filler

Colour(s)

- White

product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Packaging



- Bucket
- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

Certifications

	EN 13963: 1A
	M1
	Emicode EC1 Plus

Health & Safety

Product Safety Data Sheet must be read and understood before use.  
These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the



Den Braven

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

04-05-2024  
17:02:56  
MDT