

Technical Data Sheet

Tectane Penetrating Oil MoS2 Provides protection agains rust



Product Description

Tectane Penetrating Oil is a well-established lubricant and rust remover. Tectane Penetrating Oil effortlessly and quickly solves a number of problems with servicing, repairs, maintenance and production.

Benefits

- · Releases rusted screwed joints, nuts and bolts
- Offers long lasting corrosion protection
- · Removes squeaking and creaking noises
- Greases sliding surfaces

Applications

Tectane Penetrating Oil can be used for car maintanance, industry, household, marine, etc.

Directions Of Use

Shake can vigourously before application. Spray onto rusted surface so that all rusty parts are fully covered. Let product sit for a couple of minutes. Remove solved rust.

Additional information

Base	Hydrocarbons
Density	0.704
Extrusion rate gs	1.8
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	4.2
Pressure at 50c bar	7.9
Solid contents	<1

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Translucent

Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be





Technical Data Sheet

Tectane Penetrating Oil MoS2 Provides protection agains rust

copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All delveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

