



Technical Data Sheet

Tectane Protection Wax

Protection wax for long lasting protection



Product Description

Protection from rust in grooves and on surfaces. It offers long-lasting protection from corrosion, oxidation and dirt. When the wax has dried it leaves a sticky, plasticine-like, water-repellent film which is almost colourless. Saltwater and heat-resistant (100°C).

Benefits

Applications

It's excellent flow properties make it suitable for inaccessible areas. Protection Wax is used for preserving grooves, surfaces and cavities in motor vehicles, building machinery, agricultural implements as well as for household and garden gadgets. Its light colour makes it particularly suitable for the protection of grooves in car bonnets and boots. It is suitable for both a secondary treatment, such as after an accident, and a first treatment. It is also a preferred means of preserving an engine compartment that has just been cleaned.

Directions Of Use

Before use, pre-treat, if necessary, with a cleaner, primer or Zinc-Aluminium Spray. Apply wax as a thin layer and allow to dry. Plastic and rubber are not affected.

Additional information

Base	siloxane
Density	0.616
Extrusion rate gs	1.0
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	3
Pressure at 50c bar	5.9
Solid contents	<1

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Colourless

Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between $+5^{\circ}$ C and $+25^{\circ}$ C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be





Technical Data Sheet

Tectane Protection Wax

Protection wax for long lasting protection

copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

