



Zwaluw Window Foil Interior

An Airtight flexible interior window foil

Product Description

Zwaluw Window Foil Interior is an airtight, tear-proof, highly flexible fleece fabric, with an integrated self-adhesive affixing strip. Zwaluw Window Foil Interior complies with the planning and installation recommendations of DIN 4108-7 and with the RAL Quality Assurance Association for windows and doors. Zwaluw Window Foil Interior can be plastered and painted over if necessary.

Benefits

Applications

Zwaluw Window Foil Interior can be used in order to achieve an airtight connection between the window frame and the building construction. To apply the flexible fleece fabric to the building construction, we recommend Zwaluw Montagefix-W for indoor applications and Zwaluw Foliefix@SPUR for outdoor applications. Zwaluw Window Foil Interior does have an a value of 0,00299 m³/[h.m (daPa)n] and an Sd value of 39 m.

Directions Of Use

Additional information

Application temperature		+5°C to +30°C
Elongation at break		1.34
Fire behaviour		B2
Frost resistance during transportation		Up to -15°C
Joint permeability	EN 1027	>600 Pa
Permeability	EN 1026	a = 0,00083 m ³ /h.m
SD Value	DIN 4108 T.3	39 m
Temperature resistance		-40°C to +80°C

These are typical values

Limitations

Surface Preparations and Finishing

Before using the Zwaluw Window Foil Interior refer to the Health & Safety Sheet. All surfaces must be clean, dry and free of dust, grease

and other loose material. Thoroughly clean by using Zwaluw Cleaner and two cloths. Contact Den Braven for a full recommendation. Unroll the Zwaluw Window Foil Interior and cut it so that there is an excess length of approx. 5cm. Pull off the covering film and carefully press the affixing strip against the back of the window. Repeat on all of the sides of the window which are to be sealed. Align the window element and fix in place before filling out the cavity space between the window and the wall with Zwaluw NBS Flex-foam. For adherence to the masonry substrate, we recommend the use of Zwaluw Montagefix-W for indoor applications and Zwaluw Foliefix@SPUR for outdoor applications. Ensure that the plaster in the door area is sufficiently cloth-reinforced. We recommend Zwaluw Compress Band BG-1 or Zwaluw Window Foil Exterior for an external heavy rainproof, vapour diffusion sealing.

Paintability

Zwaluw Window Foil Interior can be painted and plastered.

Cleaning

Colour(s)

- Reddish/Pink

Packaging


- Roll

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 12 months when stored as recommended in original unopened packaging.

Certifications

	Emicode EC1 Plus
	A+ (Eurofins ISO 16000)





Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw Window Foil Interior

An Airtight flexible interior window foil

Health & Safety

Product Safety Data Sheet must be read and understood before use.
These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.