



Den Braven

Technical Data Sheet

Zwaluw Butylrubber-W

Plasto-elastic non corrosive sealant



Product Description

Zwaluw Butylrubber-W is a durable plastic-elastic water based sealant for ducting applications. The product cures by evaporation of water from the sealant.

Benefits

- Flexible
- Waterbased
- Easy to clean

Applications

Zwaluw Butylrubber-W was developed for joints that are exposed to low movement in air-conditioning systems. Also for use in the building, cooling, and automotive industries. Other applications are bedding compounds for sandwich panels and corrugated iron, profiles, strips, window and doorframes in mobile and static caravans. Also for use in joints in metal construction, in ship and coach building, bedding of wooden profiles.

Directions Of Use

For a complete overview see our website or contact Den Braven.

Additional information

Application temperature		+5°C to +40°C
Base		Butyl rubber
Curing time	@ +23°C/50% RH	24 hours
Density		1,23 g/ml
Frost resistance during transportation		Up to -15°C
Skinning time	@ +23°C/50% RH	10-20 minutes
Temperature resistance		-20°C to +75°C

These are typical values

Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Surfaces must be clean, dry and structurally sound. Primer is not necessary.

Cleaning

Colour(s)

- Grey

Packaging

- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

Store between +5°C and +25°C and in shaded conditions. Shelf life is up to 9 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites



Den Braven

Technical Data Sheet

Zwaluw Butylrubber-W

Plasto-elastic non corrosive sealant

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Bostik Benelux B.V
Denariusstraat 11, 4903 RC Oosterhout
T +31 (0)162491000 | E info@bostik.com

02-05-2024
16:17:36
MDT