

Bostik Easipower Plus Combi 400-600

Very reliable, professional, electric sealant and adhesive caulking gun



Product Description

Easipower Plus Combi 400-600 is a reliable, professional, electric sealant and adhesive caulking gun for cartridges and sausages up to 600ml.

Benefits

- Maximum Thrust: 2.5kN
- Voltage: 10.8V
- Battery Capacity: 1.5Ah
- Battery Charge Time: 30 min.
- Battery Type: Li-ion
- Handle Material: PC/ABS
- Barrel Material: Anodized Aluminum Cartridge
- Viscosity: Low/Medium
- Auto-reverse function
- Maximum rack speed of 8.0mm/sec
- Trigger lock
- Variable speed trigger
- Overload shut off function
- Stops material flow when trigger is released
- Gives higher material output
- Prevents accidental discharge of material
- For greater speed control during dispensing
- Prevents damage to the tool and material container
- Gives you long worry free performance

Applications

Capacity: 290ml, 310ml

Sausage Capacity: 400ml, 600ml

Directions Of Use

SACHET usage: Ensure the battery is not attached. Unscrew the barrel from the handle. Using an adjustable or fix size spanner loosen the nuts behind the steel plunger cap. Slide the cap back and undo and remove the front nut. Insert the blue plastic plunger cap onto the rod and secure it by replacing the ends nut onto the rod so it fits neatly into the recess of the plastic plunger. Take an adjustable or fix size spanner to the rear nuts and tighten it. Re-attach, screw in and tighten the barrel to the handle. Prepare the sachet: hold the sachet firmly in one hand and use a cutter in the other hand to cut off the tip of the sachet. Insert the sachet into the applicator. Insert the nozzle into the front cap and screw it carefully onto the front of the barrel, do not overtighten. Using the sharp blade holding away from your body cut the tip off the nozzle. Re-insert the battery. With a steady squeeze of the trigger slowly move the nozzle over to the area where required.

CARTRIDGE usage: Ensure the battery is not attached. Unscrew and remove the barrel. Using an adjustable or fix size spanner loosen the nuts behind the steel plunger cap. Remove the blue plastic plunger cap and its retaining nut. Move the steel plunger cap and the lower nut forward on the plunger, then replace the end nut securing the steel plunger cap to the plunger and retighten. Re-attach and tighten the barrel to the handle. Prepare the cartridge by holding the cartridge firmly against the hard surface and with a sharp blade holding away from your body cut the sealing cap off the cartridge. Firmly screw the cartridge nozzle onto the cartridge. Remove front barrel cap and insert the cartridge into the applicator. Re-attach the front cap to the barrel making sure not to overtighten. Using the sharp blade holding away from your body cut the tip off the nozzle. Re-insert the battery. With a steady squeeze of the trigger slowly move the nozzle over to the area where required. Application speed can be changed by varying pressure on the trigger.

Limitations

Surface Preparations and Finishing

Not applicable.

Paintability

Not applicable.

Cleaning

Depends on the type of sealant used. Use the instructions provided by the sealant manufacturer. For better result remove the sealant from the gun as early as possible.

Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162491000, E-mail: info@bostik.com
www.bostik.com | www.denbraven.com

17-05-2024
10:13:30
CEST



Bostik Easipower Plus Combi 400-600

Very reliable, professional, electric sealant and adhesive caulking gun

Colour(s)

- Grey + Black

Packaging

- Piece

For product specifications, please refer to the Product Detail Page

Shelf Life

Not applicable.

Health & Safety

Product Safety Data Sheet must be read and understood before use.

These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands

Phone: +31 (0)162491000, E-mail: info@bostik.com

www.bostik.com | www.denbraven.com

17-05-2024
10:13:30
CEST