

Bostik H14

Manual bead dispenser for cartridges



Product Description

A 1-component manual bead dispenser for 310ml cartridges.

Benefits

- Lightweight: 0.77kg / 1.70lbs
- Frame Length: 243mm / 9.5in
- Maximum Thrust: 1.5kN (stroke 9.8mm)
- Handle Material: Reinforced Nylon
- Frame Material: Steel
- Mechanical Advantage Ratio: (12:1)
- Viscosity: Low/Medium
- Nozzle Dimension: ø25.5mm / 1.0in
- Anti-drip and trigger integrated brake release
- Steel frame cartridge holder
- Ergonomic handle
- Fast, reliable and easy handling
- Automatic cartridge positioning and fixation

Applications

Suitable for 310ml cartridges.

Directions Of Use

Pull the rod as far back as you can and hold it. Insert the caulking tube with the nozzle facing away. Push the back of the metal rod into the cartridge. Cut the front of the nozzle at a 45-degree angle to adjust the thickness of applied sealant. Pull the trigger and move the gun over a chosen surface. Pay attention that a handle shall be pushed forward to release the pressure

Limitations

Surface Preparations and Finishing

Not applicable.

Paintability

Not applicable.

Cleaning

Depends on the type of sealant used. Use the instructions provided by the sealant manufacturer. For better result remove the sealant from the gun as early as possible.

Colour(s)

- red and black

Packaging

- Piece

For product specifications, please refer to the Product Detail Page

Shelf Life

Not applicable.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162491000, E-mail: info@bostik.com
www.bostik.com | www.denbraven.com

17-05-2024
06:20:08
MDT