



Den Braven

Technical Data Sheet

Zwaluw Parketfix MSPS 001

1-component floor adhesive



Product Description

Zwaluw Parketfix MSPS 001 is a 1-component moisture curing trowel applied adhesive for full surface floor adhesive.

Benefits

- Fast curing
- Permanent elasticity
- Easy to apply
- Excellent strength

Applications

Zwaluw Parketfix MSPS 001 was specifically designed for laying solid and engineered wood flooring (strips, longstrips, planks, panels, boards) mosaic parquet, industrial parquet, wood paving (residential) as well as chipboard.

Directions Of Use

Additional information

100 % modulus	ISO 37	± 0,90 N/mm ²
Application rate	@ Ø4 mm/3 bar	0,8-1,5 kg/m ²
Application temperature		+5°C to +40°C
Base		Hybride
Curing time	@ +23°C/50% RH	3mm/24 hours
Density	ISO 1183-1	1,50 g/ml
Shearing strength	ISO 4587	± 0,8 N/mm ²
Shorea hardness	ISO 868	± 40
Skin formation	@ +23°C/50% RH	± 45 minutes(@ +23°C/50% RH)
Temperature resistance		-30°C to +70°C
Viscosity		± 40000 mPa.s

These are typical values

Limitations

- Avoid contact with alcohol and other solvent cleaners during curing
- Do not allow to harden in the presence of uncured silicone sealants
- A humid environment is required for correct curing

Surface Preparations and Finishing

The subfloor must be structurally sound, clean, dry, level and free of oils, bituminous materials, curing compounds, grease, dust, loose particles, paint and other poorly adhering material. All concrete, cement screed and gypsum based sub-floors must be structurally sound, clean, dry, level, free of voids, projections, loose materials, oil, grease, sealers and other surface contaminants, they should be thoroughly cleaned with an industrial vacuum. For application over ceramic tiles, it is necessary to grind tile substrates, removing any glaze and producing a matt, fine gripping surface, then clean thoroughly with an industrial vacuum.



Den Braven

Bostik Benelux B.V.
Denariusstraat 11, 4903 RC Oosterhout
T +31 (0)162491000 | E info@bostik.com

04-05-2024
14:00:23
MDT



Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw Parketfix MSPS 001

1-component floor adhesive

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner.

Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

- Oak

Packaging

- Plastic pail

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life up to 6 months from production date, stored in a dry place.

Certifications

	A+ (Eurofins ISO 16000)
--	-------------------------

Health & Safety

Product Safety Data Sheet must be read and understood before use.

These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Bostik Benelux B.V
Denariusstraat 11, 4903 RC Oosterhout
T +31 (0)162491000 | E info@bostik.com

04-05-2024
14:00:23
MDT