

Bostik Jetflow 3 Compact Combi

1-component closed pneumatic bead and spray caulking gun



Product Description

Jetflow 3 Compact Combi is a 1-component closed pneumatic bead and spray caulking gun for cartridges of 310ml, 400ml and 600ml sausages.

Benefits

- Weight: 1.76kg / 3.9lbs
- Barrel Length: 535.8mm / 21in
- Maximum Thrust: 1.45kN
- Maximum Pneumatic Pressure: 6.8bar (100psi)
- Handle Material: Glass Filled Nylon
- Barrel Material: Aluminum
- Viscosity: Low/Medium
- Variable speed regulator
- Built-in silencer (less than 70dB)
- Ergonomically designed for comfort
- For precise control and smooth material flow
- Easy adjustment between bead and spray
- Lowers the noise level
- Gives you long worry free performance

Applications

Cartridge capacity: 310ml

Sachet Capacity: 310ml, 400ml, 600ml

Directions Of Use

CARTRIDGE: Remove the protective dust cap. Fit the suitable airline coupling adaptor for your air system and tighten using a spanner.

Unscrew the black front cap. Firmly screw the cartridge nozzle onto the cartridge. Insert the cartridge with the nozzle facing away.

Replace the black front cap. Cut the front of the nozzle at a 45-degree angle to adjust the thickness of applied sealant. Attach the air supply. Push the trigger to start to apply the sealant. By turning the wheel at the top of the black end cap, you can control the output flow of

adhesive or sealant. **SACHET:** Unscrew the black end cap. Take out the black plastic cork. Place the sachet accessory blue cork in. Push it forward and place the black plastic cork back. Screw back the black end cap on the gun. Remove the protective dust cap. Fit the suitable airline coupling adaptor for your air system and tighten using a spanner. Unscrew the black front cap. Firmly screw the cartridge nozzle onto the cartridge. Insert the cartridge with the nozzle facing away. Replace the black front cap. Cut the front of the nozzle at a 45-degree angle to adjust the thickness of applied sealant. Attach the air supply. Push the trigger to start to apply the sealant. By turning the wheel at the top of the black end cap, you can control the output flow of adhesive or sealant.

Limitations

Surface Preparations and Finishing

Not applicable.

Paintability

Not applicable.

Cleaning

Depends on the type of sealant used. Use the instructions provided by the sealant manufacturer. For better result remove the sealant from the gun as early as possible.

Colour(s)

- Grey + Black

Packaging

- Piece

For product specifications, please refer to the Product Detail Page

Shelf Life

Not applicable.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162491000, E-mail: info@bostik.com
www.bostik.com | www.denbraven.com

16-05-2024
21:04:01
MDT



Bostik Jetflow 3 Compact Combi

1-component closed pneumatic bead and spray caulking gun

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Bostik Benelux B.V
Denariusstraat 11, 4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162491000, E-mail: info@bostik.com
www.bostik.com | www.denbraven.com

16-05-2024
21:04:01
MDT