



Den Braven

Technical Data Sheet

Zwaluw Tixoplast®

1-component bitumen based sealant



Product Description

Zwaluw Tixoplast® is a 1-component bitumen based sealant which cures to a plastic seal by evaporation of the solvent.

Benefits

Applications

Zwaluw Tixoplast® was developed as an adhesive for bituminous roofing and insulation panels (not of polystyrene), weatherproof sealing of joints, eaves, gutters, skylights, chimneys, etc. Zwaluw Tixoplast® can also be used as sealing for leaks, emergency repairs even in wet weather. Also for filling of cracks, joints and blisters on roofs and gutters in roofing, zinc and to adhere shingles to sloped roofs.

Directions Of Use

Additional information

Application temperature		+5°C to +40°C
Base		Bitumen
Density		1,30 g/ml
Frost resistance during transportation		Up to -15°C
Temperature resistance		-20°C to +70°C

These are typical values

Limitations

- Not suitable for PE, PP, PC, PMMA and PTFE

Surface Preparations and Finishing

Application temperature +5°C to +40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Substrates to be free of dust and loose particles. Non-porous substrates do not need to be absolutely dry. Always test adhesion prior to application.

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

- Black

Packaging

- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

Store between +5°C and +25°C and in shaded conditions. Shelf life is up to 9 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the



Den Braven

Bostik Benelux B.V.
Denariusstraat 11, 4903 RC Oosterhout
T +31 (0)162491000 | E info@bostik.com

08-05-2024
23:51:01
CEST



Den Braven

Technical Data Sheet

Zwaluw Tixoplast®

1-component bitumen based sealant

product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

Better
results
through
knowledge