



Technical Data Sheet

Zwaluw Elast-O-Rub

A versatile non filled sealant



Product Description

Zwaluw Elast-O-Rub is a versatile non filled sealant based on Styrol-Blokcopolymer (S-EB-S) which cures by evaporation of solvents to a soft plastic elastic rubber.

Benefits

- · Adheres to most, even damp, surfaces
- Paintable with most water based and synthetic paints

Applications

Zwaluw Elast-O-Rub was developed for temporary repairs of joints and cracks between stone, concrete and metal. Also suitable for repairing leaks in gutters and other water proofings.

Directions Of Use

Additional information

100 % modulus	N/mm2	0,5
Application temperature		+5°C to +40°C
Base		Synthetic rubber
Density		0,95 g/ml
Shorea hardness	DIN 53505	25 ± 5
Shrinkage		approximately 20%
Skin formation	@ +23°C/50% RH	3-5 minutes
Temperature resistance		-25°C to +100°C

These are typical values

Limitations

• Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Application temperature: +5°C to +40°C (applies to environment and substrates). All substrates must be solid, clean and free of grease and dust. Clean substrates with Zwaluw Cleaner. Zwaluw Elast-O-Rub adheres perfectly without the use of primer to most non porous substrates. Always test adhesion prior to application.

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

Transparent

Packaging

Cartridge

For product specifications, please refer to the Product Detail Page







Technical Data Sheet

Zwaluw Elast-O-Rub

A versatile non filled sealant

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 24 months after date of production, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites.

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik's written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.