



Technical Data Sheet

Tectane Cockpit Spray Silicone free



Product Description

Tectane Cockpit Spray is a multi-purpose product. It is used for maintaining and servicing electric installations in motor vehicles. A single treatment with QTA302.3M is sufficient in most cases and saves a lot of time!

Benefits

- Protects from dirt, frictional electricity & moisture
- · Spreads a pleasant smell in the car
- Dust-repellent

Applications

Tectane Cockpit Spray can be used in the field of motor vehicles, electricity and electrical engineering for maintaining electric installations, such as electric contacts, fuses, spark plug sockets, distributors, cable connections & trailer coupling and cable plugs for jump leads.

Directions Of Use

Shake can well before use. Spray sparingly onto parts to be cleaned and immediately use a soft cloth to spread without applying pressure. Do not spray onto steering wheel, pedals, seats or arm-rests!

Additional information

Application temperature	+5°C to +25°C
Base	Fatty Acids/ hydrocarbon solvent
Density	0.647
Extrusion rate gs	1.0
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	4.9
Pressure at 50c bar	9

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Colourless

Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between $+5^{\circ}$ C and $+25^{\circ}$ C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.







Technical Data Sheet

Tectane Cockpit Spray Silicone free

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.