



Den Braven

## Technical Data Sheet

### Tectane Rust Primer Red Brown

Alkyd-resin-based, fast-drying



#### Product Description

Tectane Rust Primer Red Brown is a fast drying corrosion protection primer. It has excellent rust protection abilities.

#### Benefits

#### Applications

#### Directions Of Use

All surfaces must be dry, clean and free from dirt or corrosion. Surfaces should be at room-temperature, if possible. Shake can vigorously for approx. 3 min or until the mixing balls are audible. Apply cross-wise in several layers with a distance of approx. 15-20 cm.

#### Additional information

Application temperature	+16°C to +25°C
Base	Alkyd-resin
Curing time	24 hours
Density	0.824
Dust free after min	70
Extrusion rate gs	1.5
Film thickness coverage_m	50
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	3.7
Pressure at 50c bar	7.3
Re-coatable after hrs	24
Solid contents	23.8
Tack free time	35-40 minutes
Temperature range_c	-25°C to +80°C

*These are typical values*

#### Limitations

#### Surface Preparations and Finishing

Surfaces have to be clean, dry and free of grease, rust and loose particles.

#### Paintability

Paintable with most lacquers and paints, test prior to application.

#### Cleaning

#### Colour(s)

- Red

#### Packaging

- Aerosol

*For product specifications, please refer to the Product Detail Page*



# Den Braven

Better  
results  
through  
knowledge

## Technical Data Sheet

### Tectane Rust Primer Red Brown

Alkyd-resin-based, fast-drying

#### Shelf Life

Store between +5°C and +25°C in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

#### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



Den Braven

Bostik Singapore  
1 Science Park Road, #04-01/5 The Capricorn, 117528 Singapore  
T +65 6419 9161 | E

20-05-2024  
13:07:35  
MDT