



Technical Data Sheet

Tectane Silicone Spray Anti-oxidising silicone spray



Product Description

Silicone Spray is a fat-free lubricant, protective and parting agent as well as conditioner.

Benefits

- · Protects from corrosion and oxidation
- · Water-repellant
- · Clean, non-hardening lubrication film
- High resistance to temperatures
- Rubber parts remain soft and will not freeze, become brittle or stick
- · Prevents aging of plastic parts

Applications

Has a wide range of applications owing to its properties.

Directions Of Use

Shake can vigorously. Spray on to the cleaned and degreased surface from a distance of 20-30 cm and rub with a soft cloth.

Additional information

Base	Silicone oil
Density	0.579
Extrusion rate gs	1.1
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	5.6
Pressure at 50c bar	10.7

These are typical values

Limitations

Surface Preparations and Finishing

Cleaning

Colour(s)

Translucent

Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness







Technical Data Sheet

Tectane Silicone Spray Anti-oxidising silicone spray

of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.