

## Bostik FP312 Fire Retardant Coating

### FIRE RETARDANT ABLATIVE COATING



#### Product Description

Sprayable ablative coating specially designed to enhance, seal and fire protect stone wool fibres. The coating dries to give a flexible white surface finish. Stone wool fibres coated with Bostik FP312 Fire Retardant Coating prevent the spread of fire and smoke through openings in fire rated walls and floors where openings are formed to allow the installation of multiple building services. The system will contribute maintaining the acoustic design performance. Bostik FP312 Fire Retardant Coating is based on a durable polymer system with inert fillers, non-halogenated fire retardants and a preservative to resist microbial attack. Bostik FP312 Fire Retardant Coating is designed to be applied via spraying directly onto mineral fibres. The coating dries to give a sound, flexible white surface finish. During installation of mineral fibres, the cured sealant coating reduces delamination and increases surface stability for adhesive and fixing sealant application. **LIMITATIONS** - As Bostik FP312 Fire Retardant Coating is water based, in cases where corrosion protection is a problem; some metals may require a barrier between the coating and the metal surface prior to installation. - Bostik FP312 Fire Retardant Coating is not intended for application on bituminous substrates or substrates that can extrude certain oils and plasticizers or solvents. - The coating is not recommended for use in submerged joints or areas exposed to high abrasion. Available on request: - Material safety data sheet - ETA 19/0393 & ETA 19/0394

#### Benefits

- CE-marked
- Easy to apply - spray grade
- Up to 4-hour fire resistance
- High sound insulation
- Certified to the latest European standard EN 1366-3 & 4
- CE Marked to ETAG 026-2&3
- Fire resistance up to 4 hour

- Permanently flexible - will accommodate movements during fire and smaller movements in the construction it has been fitted within
- Easy and very quick to apply
- The coating applied on mineral fibres is classified for all types of constructions with or without building service penetrations
- May be used in unlimited lengths in walls with heights up to 1200 mm and in floors with widths up to 120 mm
- May be installed in gypsum walls without framing around the opening
- Easy to clean
- Once fully cured, resistant of water and frost
- Complies with requirements of M1 Protocol

#### Applications

The ablative property of Bostik FP312 Fire Retardant Coating resists flame spread and protects the mineral fibres against fire penetration by significantly reducing the permeability of the mineral fibre core and prevents the passage of hot gases, thus reducing the temperature rise on the unexposed side and reducing heat conduction through the building services. Mineral fibres coated with Bostik FP312 Fire Retardant Coating are designed to prevent the spread of fire and smoke through openings in fire rated walls and floors, also where openings are formed to allow the installation of multiple building services. The system will also maintain the acoustic design performance.

Suitable for most surfaces, included concrete, masonry, steel, gypsum, glass, plastics and most non-porous surfaces. Bostik FP312 Fire Retardant Coating can be applied in combination with e.g. Bostik FP310 Intumescent Acoustic Acrylic, Bostik FP320 Fire Batt and Bostik FP340 Pipe Wrap.

#### Directions Of Use

Before applying Bostik FP312 Fire Retardant Coating on the stonewool core ensure that the surface of all surrounding constructions is free from all loose contaminants, dust and grease. The stonewool should be dry and sound, and any large loose pieces should be brushed off before applying/ spraying. To secure high density stonewool boards, seal between the stonewool and the surface of all surrounding constructions on both sides with Bostik FP310 Intumescent Acoustic Acrylic which will act as an adhesive. Spray or brush Bostik FP312 Fire Retardant Coating to the stonewool

#### Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands  
Phone: +31 (0)162491000, E-mail: [info@bostik.com](mailto:info@bostik.com)  
[www.bostik.com](http://www.bostik.com) | [www.denbraven.com](http://www.denbraven.com)

17-05-2024  
11:44:47  
CEST

## Bostik FP312 Fire Retardant Coating

### FIRE RETARDANT ABLATIVE COATING

in smooth strokes and with the minimum of overapplication to achieve an even wet film thickness and consistent drying across the stonewool. The minimum required wet film thickness is 1.0mm and is usually achieved when the surface is to a satisfactory proper white finish when dry. Overapplication can increase drying times. Drying times will depend on film thickness, ambient temperature and humidity and may be reduced by using drying ovens and/or fans. Bostik FP312 Fire Retardant Coating can be over-painted with most water based and synthetic paints. Tools should be cleaned after use with water. Hands can be cleaned with water and soap. Before application consult the installation instructions and ETAs to ensure to achieve the intended fire resistance.

#### Additional information

Application temperature		+10°C to +30°C
Base		Durable polymer system
Curing time		3 to 5 days depending on thickness and temperature
Density	ISO 1183-1	1.35 g/ml
Fire rating		EN 1366-3 & EN 1366-4
Temperature resistance		-30°C to +80°C
Usage		1,08 m2/kg

*These are typical values*

#### Limitations

- Do not use in areas with prolonged exposure to water

#### Surface Preparations and Finishing

#### Paintability

Paintable with most water based and alkyd paints.

#### Cleaning

#### Colour(s)

- White

#### Packaging



- Plastic pail

*For product specifications, please refer to the Product Detail Page*

#### Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life is up to 12 months from production date, stored in a dry place.

#### Certifications

	EN 1366-3 EN 1366-4:2006+A1:2010
	A+ French VOC Regulation
	Emicode EC1 Plus

#### Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

#### Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

#### Bostik Benelux B.V

Denariusstraat 11, 4903 RC Oosterhout, The Netherlands  
Phone: +31 (0)162491000, E-mail: [info@bostik.com](mailto:info@bostik.com)  
[www.bostik.com](http://www.bostik.com) | [www.denbraven.com](http://www.denbraven.com)

17-05-2024  
11:44:47  
CEST